

DIFFERENTIAL EQUATIONS
AND
CONTROL PROCESSES
N 2, 2010
Electronic Journal,
reg. N Φ C77-39410 at 15.04.2010
ISSN 1817-2172

http://www.math.spbu.ru/diffjournal http://www.neva.ru/journal e-mail: jodiff@mail.ru

Exponential stability of linear uncertain polytopic systems with distributed time-varying delays

LE VAN HIEN

Department of Mathematics, Hanoi National University of Education 136 Xuan Thuy, Cau Giay, Hanoi, Vietnam E-mail: Hienly@hnue.edu.vn

Abstract

In this paper, a class of uncertain linear polytopic systems with distributed time varying delays is studied. By using an improved parameter dependent Lyapunov-Krasovskii functional approach and linear matrix inequality technique, delay-dependent sufficient conditions for exponential stability of the system are first established in terms of Mondie-Kharitonov type's linear matrix inequalities (LMIs). Numerical example is presented to demonstrate the effectiveness of the proposed conditions.

Keywords: polytopic uncertainty; exponential stability; distributed delays; linear matrix

inequality.

2000MSC: 34D05, 34D20, 34K20, 34K35

1 Introduction

The stability analysis of linear time-delay systems is a topic of great practical importance, which has attracted a lot of interest over the decades (see e.g. [1, 2, 3, 5]). Also, systems uncertainties arise from many sources such as unavoidable approximation, data errors and aging of systems and so the stability issue of uncertain time delay systems has been investigated by many researchers (see

[6, 8, 9]), where the Lyapunov-Krasovskii functional method is certainly used as the main tool.

Recently, the stability analysis of linear system with polytopic type uncertainties has also received much attention (see e.g. [4, 8, 10]). However, the distributed delays are not considered in the mentioned papers. In practice, systems with distributed delays have many important applications in various areas (see [2, 3]). Theoretically, systems with distributed delays are much more complicated, especially for the case where the system matrices belong to some convex polytope. To the best of our knowledge, so far, no result on the stability for uncertain linear polytopic systems with distributed delays is available in the literature. This motivates our present investigation.

In this paper, we develop the robust stability problem for linear uncertain polytopic systems with discrete and distributed time varying delays. The novel feature of the results obtained in this paper is twofold. First, the system considered in this paper is convex polytopic uncertain subjected to discrete and distributed time varying delays. Second, by employing an improved parameter dependent Lyapunov-Krasovskii functional and linear matrix inequality technique, delay dependent sufficient conditions for the exponential stability of the system are obtained in terms of the Mondié-Kharitonov type's LMI conditions [7]. The approach also allows to compute simultaneously the two bounds that characterize the exponential stability rate of the solution.

The paper is organized as follows: Section 2 presents notations, definitions and a well-known technical proposition needed for the proof of the main result. Delay dependent exponential stability conditions of the system and numerical example is presented in Section 3. The paper ends with conclusions and cited references.

2 Preliminaries

The following notations will be employed throughout this paper: A^{T} denotes the transpose of A, $\lambda(A)$ denotes the set of all eigenvalues of A, $\lambda_{\max}(A) = \max\{\operatorname{Re} \lambda : \lambda \in \lambda(A)\}$, $\lambda_{\min}(A) = \min\{\operatorname{Re} \lambda : \lambda \in \lambda(A)\}$; matrix $Q \geq 0$ (Q > 0, resp.) means Q is semi positive definite matrix i.e. $\langle Qx, x \rangle \geq 0, \forall x \in R^n$ (positive definite, resp. i.e. $\langle Qx, x \rangle > 0, \forall x \in R^n, x \neq 0$), $A \geq B$ means $A - B \geq 0$; $C([a, b], R^n)$ denotes the set of all R^n -valued continuous functions on [a, b]; the segment of the trajectory x(t) is denoted by $x_t = \{x(t+s) : s \in t \in [-h, 0]\}$ with its norm $\|x_t\| = \sup_{s \in [-h, 0]} \|x(t+s)\|$.

Consider a linear uncertain polytopic system with discrete and distributed time varying delays of the form

$$\dot{x}(t) = A(\sigma)x(t) + B(\sigma)x(t - h(t)) + D(\sigma) \int_{t - \tau(t)}^{t} x(s)ds, \ t \ge 0,$$

$$x(t) = \phi(t), \quad t \in [-\bar{h}, 0],$$
(2.1)

where $x(t) \in \mathbb{R}^n$ is the state, $h(t), \tau(t)$ are time varying delay functions which are continuous and satisfying

$$0 \le h(t) \le h, \quad 0 \le \tau(t) \le \tau \quad \dot{h}(t) \le \mu < 1, \quad \dot{\tau}(t) \le \delta < 1 \tag{2.2}$$

and $\bar{h} = \max\{h, \tau\}$. The system matrices $[A(\sigma), B(\sigma), D(\sigma)]$ are subject to uncertainties and belong to the polytope Ω given by

$$\Omega = \left\{ [A, B, D](\sigma) = \sum_{i=1}^{p} \sigma_i [A_i, B_i, D_i], \sigma_i \ge 0, \sum_{i=1}^{p} \sigma_i = 1 \right\},\,$$

where $A_i, B_i, D_i \in R^{n \times n}$, i = 1, 2, ..., p, are given real matrices; $\phi(t) \in C([-\bar{h}, 0], R^n)$ is the initial function with the norm $\|\phi\| = \sup_{-\bar{h} \le s \le 0} \|\phi(s)\|$.

Definition 2.1. For a given $\alpha > 0$, system (2.1) is said to be α -exponentially stable if there exist a number $\gamma \geq 1$ such that every solution $x(t, \phi)$ of system (2.1) satisfies the following condition

$$||x(t,\phi)|| \le \gamma ||\phi|| e^{-\alpha t}, \quad \forall t \ge 0.$$

3 Main result

For positive numbers α, h, τ , symmetric positive definite matrices $P_i, Q_i, R_i \in \mathbb{R}^{n \times n}$ and semi-positive definite matrix $S \in \mathbb{R}^{n \times n}$ we denote

$$P = \sum_{i=1}^{p} \sigma_{i} P_{i}, \quad Q = \sum_{i=1}^{p} \sigma_{i} Q_{i}, \quad R = \sum_{i=1}^{p} \sigma_{i} R_{i},$$

$$\Gamma_{ij} = P_{j} A_{i} + A_{i}^{\mathsf{T}} P_{j} + Q_{j} + \tau^{2} R_{j},$$

$$\mathcal{M}_{i}(P_{j}, Q_{j}, R_{j}) = \begin{bmatrix} \Gamma_{ij} & P_{j} B_{i} & P_{j} D_{i} \\ B_{i}^{\mathsf{T}} P_{j} & -(1 - \mu) e^{-2\alpha h} Q_{j} & 0 \\ D_{i}^{\mathsf{T}} P_{j} & 0 & -\frac{(1 - \delta)}{2} e^{-2\alpha \tau} R_{j} \end{bmatrix}, \quad (3.1)$$

$$S = \begin{bmatrix} S & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}, \quad \mathcal{N}(P_{j}) = \begin{bmatrix} P_{j} & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}, \quad i, j = 1, 2, \dots, p,$$

$$\lambda_{\min}(P) = \min_{i=1, 2, \dots, p} \{\lambda_{\min}(P_{i})\}, \quad \lambda_{\max}(P) = \max_{i=1, 2, \dots, p} \{\lambda_{\max}(P_{i})\},$$

$$\lambda_{\max}(Q) = \max_{i=1, 2, \dots, p} \{\lambda_{\max}(Q_{i})\}, \quad \lambda_{\max}(R) = \max_{i=1, 2, \dots, p} \{\lambda_{\max}(R_{i})\},$$

$$\gamma_{1} = \lambda_{\min}(P), \quad \gamma_{2} = \lambda_{\max}(P) + h\lambda_{\max}(Q) + \frac{1}{2}\tau^{2}\lambda_{\max}(R).$$
(3.2)

The main result is stated in the following theorem.

Theorem 3.1. For given $\alpha > 0$. System (2.1) is α -exponentially stable if there exist positive definite matrices $P_i, Q_i, R_i, i = 1, 2, ..., p$ and a semi-positive definite matrix S such that the following LMIs hold:

i)
$$\mathcal{M}_i(P_i, Q_i, R_i) + 2\alpha \mathcal{N}(P_i) \leq -\mathbb{S}, \quad i = 1, 2, \dots, p,$$

ii)
$$\mathcal{M}_i(P_j, Q_j, R_j) + \mathcal{M}_j(P_i, Q_i, R_i) + 2\alpha \mathcal{N}(P_i + P_j) \le \frac{2}{p-1} \mathbb{S},$$

 $i = 1, \dots, p-1, j = i+1, \dots, p.$

Moreover, every solution $x(t,\phi)$ of the system satisfies

$$||x(t,\phi)|| \le \sqrt{\frac{\gamma_2}{\gamma_1}} ||\phi|| e^{-\alpha t}, \quad t \ge 0,$$

where γ_1, γ_2 are defined in (3.2).

Proof. Because $P_i > 0$, $Q_i > 0$, $R_i > 0$, $\sigma_i \ge 0$, i = 1, 2, ..., p and $\sum_{i=1}^p \sigma_i = 1$ we have $P = \sum_{i=1}^p \sigma_i P_i$, $Q = \sum_{i=1}^p \sigma_i Q_i$, $R = \sum_{i=1}^p \sigma_i R_i$ are symmetric positive definite matrices. Consider the following parameter dependent Lyapunov-Krasovskii functional for system (2.1)

$$V(x_t) = x^{\mathsf{T}}(t)Px(t) + \int_{t-h(t)}^{t} e^{2\alpha(s-t)}x^{\mathsf{T}}(s)Qx(s)ds + \int_{t-\tau(t)}^{t} \int_{s}^{t} e^{2\alpha(\zeta-t)}x^{\mathsf{T}}(\zeta)Rx(\zeta)d\zeta ds.$$

$$(3.3)$$

It can be verified from (3.3) that

$$\gamma_1 \|x(t)\|^2 \le V(x_t) \le \gamma_2 \|x_t\|^2, \quad t \ge 0,$$
 (3.4)

where γ_1, γ_2 are defined in (3.2).

Taking derivative of $V(x_t)$ along solutions of system (2.1), we get

$$\dot{V}(x_{t}) = x^{\mathsf{T}}(t)[A^{\mathsf{T}}P + PA]x(t) + 2x^{\mathsf{T}}(t)PBx(t - h(t))
+ 2x^{\mathsf{T}}(t)PD \int_{t-\tau(t)}^{t} x(s)ds + x^{\mathsf{T}}(t)Qx(t)
- (1 - \dot{h}(t))e^{-2\alpha h(t)}x^{\mathsf{T}}(t - h(t))Qx(t - h(t))
- 2\alpha \int_{t-h(t)}^{t} e^{2\alpha(s-t)}x^{\mathsf{T}}(s)Qx(s)ds
+ \tau(t)x^{\mathsf{T}}(t)Rx(t) - (1 - \dot{\tau}(t)) \int_{t-\tau(t)}^{t} e^{2\alpha(s-t)}x^{\mathsf{T}}(s)Rx(s)ds
- 2\alpha \int_{t-\tau(t)}^{t} \int_{s}^{t} e^{2\alpha(\zeta-t)}x^{\mathsf{T}}(\zeta)Rx(\zeta)d\zeta ds
\leq x^{\mathsf{T}}(t)[A^{\mathsf{T}}P + PA + Q + \tau R]x(t) + 2x^{\mathsf{T}}(t)PBx(t - h(t))
+ 2x^{\mathsf{T}}(t)PD \int_{t-\tau(t)}^{t} x(s)ds - (1 - \mu)e^{-2\alpha h}x^{\mathsf{T}}(t - h(t))Qx(t - h(t))
+ 2x^{\mathsf{T}}(t)PD \int_{t-\tau(t)}^{t} x(s)ds - (1 - \delta)e^{-2\alpha \tau} \int_{t-\tau(t)}^{t} x^{\mathsf{T}}(s)Rx(s)ds
- 2\alpha(V(x_{t}) - x^{\mathsf{T}}(t)Px(t)).$$
(3.5)

By using the fact that

$$-\int_{t-\tau(t)}^{t} x^{\mathsf{T}}(s) Rx(s) ds \le -\frac{1}{\tau} \left(\int_{t-\tau(t)}^{t} x(s) ds \right)^{\mathsf{T}} R \left(\int_{t-\tau(t)}^{t} x(s) ds \right)$$
(3.6)

then from (3.5) and (3.6) we have

$$\dot{V}(x_t) + 2\alpha V(x_t) \le \xi^{\mathsf{T}}(t)\Xi \xi(t), \tag{3.7}$$

where

$$\xi^{\mathsf{T}}(t) = \begin{bmatrix} x^{\mathsf{T}}(t) & x^{\mathsf{T}}(t - h(t)) & \left(\int_{t - \tau(t)}^{t} x(s) ds \right)^{\mathsf{T}} \end{bmatrix},$$

and

$$\Xi = \begin{bmatrix} A^\mathsf{T} P + PA + 2\alpha P + Q + \tau R & PB & PD \\ B^\mathsf{T} P & -(1-\mu)e^{-2\alpha h}Q & 0 \\ D^\mathsf{T} P & 0 & -\frac{1-\delta}{\tau}e^{-2\alpha \tau}R \end{bmatrix}.$$

By using properties

$$P = \sum_{i=1}^{p} \sigma_i P_i, \quad Q = \sum_{i=1}^{p} \sigma_i Q_i, \quad R = \sum_{i=1}^{p} \sigma_i R_i, \quad \sum_{i=1}^{p} \sigma_i = 1,$$

and from conditions (i) and (ii) of Theorem 3.1 we have

$$\Xi = \sum_{i=1}^{p} \sigma_{i}^{2} \left[\mathcal{M}_{i}(P_{i}, Q_{i}, R_{i}) + 2\sigma \mathcal{N}(P_{i}) \right]
+ \sum_{i=1}^{p-1} \sum_{j=i+1}^{p} \sigma_{i} \sigma_{j} \left[\mathcal{M}_{i}(P_{j}, Q_{j}, R_{j}) + \mathcal{M}_{j}(P_{i}, Q_{i}, R_{i}) + 2\alpha \mathcal{N}(P_{i} + P_{j}) \right]
\leq - \sum_{i=1}^{p} \sigma_{i}^{2} \mathbb{S} + \frac{2}{p-1} \sum_{i=1}^{p-1} \sum_{j=i+1}^{p} \sigma_{i} \sigma_{j} \mathbb{S}
= - \frac{1}{p-1} \left[(p-1) \sum_{i=1}^{p} \sigma_{i}^{2} - 2 \sum_{i=1}^{p-1} \sum_{j=i+1}^{p} \sigma_{i} \sigma_{j} \right] \mathbb{S}$$

It's easy to verify that

$$(p-1)\sum_{i=1}^{p}\sigma_i^2 - 2\sum_{i=1}^{p-1}\sum_{j=i+1}^{p}\sigma_i\sigma_j = \sum_{i=1}^{p-1}\sum_{j=i+1}^{p}(\sigma_i - \sigma_j)^2 \ge 0.$$

Therefore it follows from (3.7) that

$$\dot{V}(x_t) + 2\alpha V(x_t) \le 0, \quad \forall t \ge 0,$$

and hence

$$V(x_t) \le V(\phi)e^{-2\alpha t} \le \gamma_2 \|\phi\|^2 e^{-2\alpha t}, \quad t \ge 0.$$

Taking (3.4) into account, we finally obtain

$$||x(t,\phi)|| \le \sqrt{\frac{\gamma_2}{\gamma_1}} e^{-\alpha t} ||\phi||, \quad t \ge 0,$$

where γ_1, γ_2 are defined in (3.2). The proof of the theorem is completed.

Remark 3.1. It is worth noting that the condition (i) means the asymptotic stability of each i^{th} -subsystem, the condition (ii) implies the asymptotic stability of the ij^{th} -subsystem and if p=1 this condition is automatically removed.

Remark 3.2. As a consequent of theorem 3.1, if $\mu = 0$ and $D_i = 0, i = 1, 2, ..., p$ then the result of theorem 3.1 implies that of theorem 1 in [8].

Example 3.1. Consider uncertain linear polytopic system with distributed time varying delays (2.1), where

$$A_{1} = \begin{bmatrix} -20 & 1 \\ 0 & -15 \end{bmatrix}, \quad A_{2} = \begin{bmatrix} -30 & 0 \\ 1 & -10 \end{bmatrix}, \quad A_{3} = \begin{bmatrix} -40 & -1 \\ 0 & -40 \end{bmatrix},$$

$$B_{1} = \begin{bmatrix} 1 & 0 \\ 1 & -1 \end{bmatrix}, \quad B_{2} = \begin{bmatrix} -1 & 1 \\ 0 & 1 \end{bmatrix}, \quad B_{3} = \begin{bmatrix} -2 & 0 \\ 1 & -1 \end{bmatrix},$$

$$D_{1} = \begin{bmatrix} -1 & 1 \\ 0 & -2 \end{bmatrix}, \quad D_{2} = \begin{bmatrix} -2 & 0 \\ 1 & -1 \end{bmatrix}, \quad D_{3} = \begin{bmatrix} 1 & 1 \\ 0 & -1 \end{bmatrix}$$

and delay functions $h(t) = \sin^2 0.5t$, $\tau(t) = \cos^2 0.5t$. Then we have the upper bounds $h = \tau = 1$ and $\mu = 0.5$, $\delta = 0.5$. By using LMI toolbox of Matlab it can be verified that all LMIs in theorem 3.1 are satisfied with $\alpha = 0.5$ and

$$P_{1} = \begin{bmatrix} 0.3993 & 0.0024 \\ 0.0024 & 0.4027 \end{bmatrix}, P_{2} = \begin{bmatrix} 0.3555 & 0.0024 \\ 0.0024 & 0.4250 \end{bmatrix}, P_{3} = \begin{bmatrix} 0.3246 & 0.0025 \\ 0.0025 & 0.3797 \end{bmatrix},$$

$$Q_{1} = \begin{bmatrix} 6.7947 & -0.1060 \\ -0.1060 & 4.5724 \end{bmatrix}, Q_{2} = \begin{bmatrix} 8.4561 & -0.1254 \\ -0.1254 & 3.4611 \end{bmatrix},$$

$$Q_{3} = \begin{bmatrix} 10.7188 & 0.2262 \\ 0.2262 & 12.2987 \end{bmatrix}, R_{1} = \begin{bmatrix} 6.7947 & -0.1060 \\ -0.1060 & 4.5724 \end{bmatrix},$$

$$R_{2} = \begin{bmatrix} 8.4561 & -0.1254 \\ -0.1254 & 3.4611 \end{bmatrix}, R_{3} = \begin{bmatrix} 10.7188 & 0.2262 \\ 0.2262 & 12.2987 \end{bmatrix},$$

$$S = \begin{bmatrix} 0.1 & 0 \\ 0 & 0.1 \end{bmatrix}.$$

By theorem 3.1, system (2.1) is exponentially stable with decay rate $\alpha = 0.5$. Moreover, every solution $x(t, \phi)$ satisfies the estimation

$$||x(t,\phi)|| \le 7.6359 ||\phi|| e^{-0.5t}, \quad t \ge 0.$$

4 Conclusion

This paper has proposed new sufficient conditions for exponential stability of linear uncertain polytopic systems with distributed time varying delays. Based on an improved Lyapunov-Krasovskii parameter dependent functional, delay dependent exponential stability conditions of the system are derived in terms of the Mondié-Kharitonov type's LMIs, which allows to compute simultaneously the two bounds that characterize the exponential stability of the solution. A numerical example illustrate the effectiveness of the obtained result is given.

Acknowledgements

This work was supported by the National Foundation for Science and Technology Development of Vietnam and Hanoi National University of Education.

References

- [1] E.N. Chukwu, Stability and Time-Optimal Control of Hereditary Systems, Boston, Academic Press, 1992.
- [2] K. Gu, V. L. Kharitonov and J. Chen, Stability of Time-Delay Systems, Birkhäuser, Berlin, 2003.
- [3] J.K. Hale and S. M. Verduyn Lunel, *Introduction to Functional Differential Equations*, New York, Springer-Verlag, 1993.
- [4] Y. He, Min Wu, Jin-Hua She and Gou-Ping Liu, Parameter-dependent Lyapunov functional for stability of time-delay systems with polytopic-type uncertainties, *IEEE Trans. Aut. Contr.*, **49**(2004), 828–832.
- [5] L.V. Hien, Q.P. Ha and V.N. Phat, Stability and stabilization of switched linear dynamic systems with time delay and uncertainties, *Appl. Math. Comput.*, **210**(2009), 223–231.
- [6] L.V. Hien and V.N. Phat, Exponential stability and stabilization of a class of uncertain linear time-delay systems, *J. Franklin Inst.*, **346**(2009), 611–625.
- [7] S. Mondié and V.L. Kharitonov, Exponential estimates for retarded time-delay systems: An LMI approach, *IEEE Trans. Aut. Contr.*, **50**(2005), 268–273.
- [8] P.T. Nam and V.N. Phat, Robust exponential stability and stabilization of linear uncertain polytopic time-delay systems, *J. Control Theory Appl.*, **6**(2008), 1–8.
- [9] R.C. Oliveira and P.L. Peres, LMI conditions for robust stability analysis based on polynomially parameter-dependent Lyapunov functions, *Syst. Control Lett.*, **55**(2006), 52–61.
- [10] V.N. Phat and P.T. Nam, Exponential stability and stabilization of uncertain linear time-varying systems using parameter-dependent Lyapunov function, *Int. J. of Control*, **80**(2007), 1333–1341.